

Cloverdale Paint

S P E C I A L T Y P R O D U C T S

Kitchen & Bath paint is specifically formulated for Kitchens, Bathrooms and other areas exposed to moisture and high humidity. Also, ideal for use on woodwork and trim. Provides superior adhesion, scrubability and is resistant to stains and mildew.



KITCHEN & BATH
#0362 SERIES EGGSHELL
#0365 SERIES SEMI GLOSS
100% ACRYLIC LATEX

K
I
T
C
H
E
N
&
B
A
T
H

0362 100% Acrylic Eggshell

Designed for maximum durability, superior stain resistance and washability. Features high moisture, mildew and burnish resistance in an extremely durable finish.

INTENDED USES

A high Performance DIY Product, Institutional and Commercial Applications. Walls, Ceilings, Woodwork & Cabinets.

SUBSTRATES

Plaster, drywall, primed wood

FINISH

Eggshell - Gloss level 2
Maximum 10 units @ 60°
10 - 35 units @ 85°

CERTIFICATIONS

MPI # 138 - Architectural Latex Gloss Level 2
LEED® compliant.
Qualifies for LEED® Credit Points
Environment Canada VOC Less than 100 g/L

BASES AVAILABLE

White 03620
Deep 03621
Clear 03624

V.O.C.

Less than 100 g/L

SOLIDS

36% by volume
53% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 5.5 mils (90 - 138 microns)
Dry: 1.25 - 2.0 mils (32 - 50 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 8 hours

SPREAD / COVERAGE

291- 445 ft²/gal (7.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0013" - 0.017"

0365 100% Acrylic Semi Gloss

Designed for maximum durability, superior stain resistance and washability. Features high moisture, mildew and burnish resistance in an extremely durable finish.

INTENDED USES

A high Performance DIY Product, Institutional and Commercial Applications. Walls, Ceilings, Woodwork & Cabinets.

SUBSTRATES

Plaster, drywall, primed wood

FINISH

Semi-Gloss - Gloss Level 5
35 - 70 units @ 60°

CERTIFICATIONS

MPI # 141 - Architectural Latex Gloss Level 5
LEED® compliant.
Qualifies for LEED® Credit Points
Environment Canada VOC Less than 100 g/L

BASES AVAILABLE

White 03650
Deep 03651
Clear 03654

V.O.C.

Less than 100 g/L

SOLIDS

35% by volume
48% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 5.5 mils (91 - 140 microns)
Dry: 1.26 - 1.92 mils (32 - 48 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 12 hours

SPREAD / COVERAGE

288 - 450 ft²/gal (7.1 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0013" - 0.017"

LEED® is a registered trade mark of U.S. Green Building Council

For the most up-to-date technical information and MSDS sheets, visit our web site at www.cloverdalepaint.com

PRODUCT FEATURES

Kitchen & Bath Eggshell is formulated with the latest acrylic technology and provides maximum durability with superior stain resistance and washability. Its superior adhesion with smooth flow and leveling properties make Kitchen & Bath Eggshell the best choice where the durability of an oil base finish is required, particularly for use in kitchen and bathrooms. It is non yellowing and has low odour. This product features high moisture, mildew and burnish resistance in a fast drying, extremely durable finish. Kitchen & Bath Eggshell has excellent colour retention, gloss retention and stain resistance properties.




This product is certified by Coatings Research Group, Incorporated to meet environmentally determined performance standards established by CRGI for specific product types and to meet or exceed the VOC requirements of LEED® for most paint and coating applications. This product is environmentally preferred over traditional paints and coatings. Visit www.greenwisepaint.com to view product standards.

Qualifies for LEED® Credit Points



Cloverdale Paint stores and authorized dealers



MANUFACTURED BY



Cloverdale Paint

6950 King George Boulevard

Surrey, BC, Canada

V3W 4Z1

www.cloverdalepaint.com