

P R E M I U M P E R F O R M A N C E

P R E M I U M P E R F O R M A N C E

PRODUCT FEATURES

A premium quality finish for use on all interior walls including drywall, plaster, masonry and primed wood. Excellent hiding and application characteristics including splatter resistance, good flow and excellent leveling properties and good scrub and stain resistance. Approved under the Master Painter's Institute under categories #53, #44, #52, #54, #50 and #4 depending on the product sheen and application. All Premium Classic products are LEED® and Environment Canada VOC compliant.

PremiumClassic

Ideal for drywall, masonry, plaster and primed woodwork where a rich, durable finish is required. Formulated to provide excellent hiding and application characteristics that retains colour and provides a durable, long-lasting finish. Meets MPI and LEED® approvals for quality and Green Performance standards.



This product is certified by Coatings Research Group, Incorporated to meet environmentally determined performance standards established by CRGI for specific product types and to meet or exceed the VOC requirements of LEED® for most paint and coating applications. This product is environmentally preferred over traditional paints and coatings. Visit www.greenwisepaint.com to view product standards.

Qualifies for LEED® Credit Points

LEED® is a registered trade mark of U.S. Green Building Council



Cloverdale Paint stores and authorized dealers



MANUFACTURED BY
 **Cloverdale Paint**

6950 King George Boulevard

Surrey, BC, Canada

V3W 4Z1

www.cloverdalepaint.com

#86366

03/12

T E C H N I C A L S P E C I F I C A T I O N S

03123 Flat Acrylic Latex

Excellent hiding and application qualities. Good coverage with low light reflection. Non yellowing with high brightness.

INTENDED USES

Interior walls where masking the effects of uneven light refraction on irregular surfaces such as textured or uneven walls and ceilings is required.

SUBSTRATES

Plaster, drywall, primed wood

CERTIFICATIONS

MPI # 53 - Latex Interior Flat Gloss Level 1 LEED compliant. Less than 50 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

White 03123
Deep 03121
Clear 03124

V.O.C.

Less than 50 g/L

SOLIDS

33% by volume
53% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 4.6 mils (92 - 117 microns)
Dry: 1.1 - 1.5 mils (28 - 38 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 2 hours minimum

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0013" - 0.015"

03240 Super Eggshell Acrylic Latex

Premium quality for interior use on new construction or re-paint projects for residential commercial and institutional projects.

INTENDED USES

Formulated specifically for use as an interior wall finish. Rich low sheen minimizes the appearance of physical surface imperfections.

SUBSTRATES

Drywall, masonry, plaster and primed woodwork.

CERTIFICATIONS

MPI # 44 - Latex Interior Gloss Level 2 LEED compliant. Less than 150 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

White 03240
Deep 03241
Clear 03244

V.O.C.

Less than 150 g/L

SOLIDS

38% by volume
53% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 4.6 mils (92 - 117 microns)
Dry: 1.4 - 1.7 mils (36 - 43 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 6 hours

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0015" - 0.019"

03243 Hi Hide Eggshell Acrylic Latex

Premium quality for interior use on new construction or re-paint projects. Formulated with additional solids for increased hiding and opacity.

INTENDED USES

Formulated specifically for use as an interior wall finish. Rich low sheen minimizes the appearance of physical surface imperfections.

SUBSTRATES

Drywall, masonry, plaster and primed woodwork.

CERTIFICATIONS

MPI # 44 - Latex Interior Gloss Level 2 LEED compliant. Less than 150 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

N/A

V.O.C.

Less than 150 g/L

SOLIDS

45% by volume
61% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 4.6 mils (90 - 117 microns)
Dry: 1.4 - 1.7 mils (36 - 43 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 6 hours

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0015" - 0.019"

03823 Pearl Acrylic Latex

Premium quality, interior use rich pearl like sheen that provides a smooth even finish with a gloss level between eggshell and semi gloss.

INTENDED USES

Designed for use in hallways and other areas that require a more durable and washable finish.

SUBSTRATES

Drywall, masonry, plaster and primed woodwork.

CERTIFICATIONS

MPI # 52 - Latex Interior Gloss level 3 LEED compliant. Less than 125 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

White 03823
Deep 03821
Clear 03824

V.O.C.

Less than 125 g/L

SOLIDS

38% by volume
52% by weight

FILM THICKNESS (per coat)

Wet: 3.9 - 4.7 mils (98 - 118 microns)
Dry: 1.4 - 1.7 mils (36 - 43 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 6 hours minimum

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0015" - 0.019"

01123 Semi Gloss Acrylic Latex

Premium quality, interior use semi gloss finish that provides superior wear including scuff and dirt resistance. Ideal for high traffic areas.

INTENDED USES

Designed for use on interior hallways and ceilings that require a scrubbable semi-gloss finish.

SUBSTRATES

Drywall, masonry, plaster and primed woodwork.

CERTIFICATIONS

MPI # 54 - Architectural Latex Gloss level 5 LEED compliant. Less than 150 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

White 01123
Deep 02121 interior/exterior
Clear 02124 interior/exterior

V.O.C.

Less than 150 g/L

SOLIDS

33% by volume
43% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 4.6 mils (92 - 117 microns)
Dry: 1.2 - 1.6 mils (30 - 41 microns)

DRY TIME

Tack Free: 1 hour
Re-Coat: 8 hours minimum

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0013" - 0.015"

05250 Hi Hide Latex Drywall Sealer

Premium latex primer/sealer is a superior performing, high hiding vinyl-acrylic sealer with excellent sanding properties.

INTENDED USES

For use as a sealer on new drywall, interior masonry and to prime patching compounds. May be used under latex and oil base finish coats.

SUBSTRATES

Drywall, masonry, plaster and woodwork.

CERTIFICATIONS

MPI # 50 - Latex Interior Primer Sealer LEED compliant. Less than 100 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

N/A

V.O.C.

Less than 100 g/L

SOLIDS

30% by volume
44% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 4.9 mils (91 - 124 microns)
Dry: 1.1 - 1.5 mils (28 - 38 microns)

DRY TIME

Tack Free: 30 minutes
Re-Coat: 3 hours minimum

SPREAD / COVERAGE

325 - 450 ft²/gal (7.5 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0015" - 0.019"

05700 Latex Block Filler

Interior/exterior heavy bodied block filler designed to fill voids and reduce irregularities on new concrete block and other types of masonry.

INTENDED USES

For use on concrete block, cinder block, cement block and other types of masonry.

SUBSTRATES

Masonry.

CERTIFICATIONS

MPI # 4 - Latex Interior/Exterior Block Filler LEED compliant. Less than 50 g/L Qualifies for LEED® Credit Points Environment Canada VOC compliant

BASES AVAILABLE

N/A

V.O.C.

Less than 50 g/L

SOLIDS

50% by volume
69% by weight

FILM THICKNESS (per coat)

Wet: 12.8 - 21.4 mils (325 - 544 microns)
Dry: 7.0 - 12.0 mils (178 - 305 microns)

DRY TIME

Tack Free: 45 minutes
Re-Coat: 2 hours minimum

SPREAD / COVERAGE

65 - 115 ft²/gal (1.6 - 2.8 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .0023" - 0.029"