

Cloverdale Paint

EXTERIOR STAIN AND WOOD CARE

Rich exterior wood finishes that provide outstanding UV protection. Ideal for surfaces such as doors, railings, exterior wood furniture, soffits, siding, log homes, and hot tub surrounds.



43606 EXTERIOR URETHANE
SATIN WOOD FINISH

56614 CLEAR & 56615 CEDAR TONED
EXTERIOR WATERBORNE SATIN
WOOD FINISH

56634 EXTERIOR WATERBORNE
SEMI-GLOSS WOOD FINISH



SUNFAST WOOD FINISH #436 / #566 SERIES

TECHNICAL SPECIFICATIONS

436 Series

INTENDED USES

Ideal for exterior use. Can be used for vertical wood surfaces such as , log homes, siding, doors, trim and fences. Provides outstanding UV protection to wood and engineered wood surfaces.

CERTIFICATIONS

Environment Canada VOC.

BASES AVAILABLE

N/A

V.O.C.

Less than 524 g/L

SOLIDS

38% by volume
43% by weight

FILM THICKNESS (per coat)

Wet: 4.5 - 6.0 mils (114 - 152 microns)
Dry: 1.5 - 2.0 mils (38 - 51 microns)

DRY TIME

Tack Free: 6 hours
Re-Coat: 24 hours

SPREAD / COVERAGE

350 - 450 ft²/gal (8.0 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush or spray.
Airless tip sizes: .009" - 0.011"

CLEAN UP

Clean tools and equipment with mineral spirits. Contact your local municipality for disposal instructions.

566 Series

INTENDED USES

Ideal for exterior use. Can be used for interior applications to wood decks, furniture, shelving, cabinets, doors and other woodwork. Provides outstanding UV protection to wood and engineered wood surfaces.

CERTIFICATIONS

MPI # 194 & 195 - Varnish, Exterior, Water Based, MPI Gloss Level 4 & MPI Gloss Level 5. Environment Canada VOC.

BASES AVAILABLE

N/A

V.O.C.

Less than 250 g/L

SOLIDS

29% by volume
31% by weight

FILM THICKNESS (per coat)

Wet: 3.6 - 5.4 mils (91 - 137 microns)
Dry: 1.0 - 1.5 mils (25 - 38 microns)

DRY TIME

Tack Free: 1 hour
Re-Coat: 4 hours

SPREAD / COVERAGE

300 - 450 ft²/gal (7.4 - 11.0 m²/L)

TOOLS & TECHNIQUES

Brush, roll or spray.
Airless tip sizes: .009" - 0.011"

CLEAN UP

Clean tools and equipment with warm, soapy water. Contact your local municipality for disposal instructions.

436 SERIES PRODUCT FEATURES

Sunfast 436 Series is a clear amber sealer / topcoat that provides a rich low lustre finish that will protect and improve the beauty of natural wood. Sunfast enhances wood grains and natural tones on exterior vertical wood surfaces. Sunfast is formulated with flexible alkyd resins and penetrating transparent iron oxide pigments which provide outstanding protection against the effects of weathering. Sunfast effectively resists cracking, peeling, and damage caused by ultra violet rays from the sun. Sunfast contains an organic fungicide that resists mildew and also contains micro-crystalline waxes that add excellent water repellence properties. Sunfast is a premium wood finish designed to last.

566 SERIES PRODUCT FEATURES

Sunfast Waterborne is a clear amber sealer Modified Urethane varnish with excellent toughness, adhesion, durability and wear resistance in a low odour formulation. Provides outstanding UV protection to wood and engineered wood surfaces. Sunfast Cedar-Tone is the ideal product for use on cedar as it highlights the natural colours in the wood. 56614 and 56634 Clears should be toned with up to 2Y Colourant for maximum exterior durability. It is an environmentally friendly product with soap and water cleanup and very low VOC's (Volatile Organic Compounds).

Sunfast enhances wood grains and natural tones on exterior vertical wood surfaces and can be applied to:
Natural Wood Siding, Log Siding, Garage Doors, Entry Doors, Wood Eaves & Trim, Wood Railings, Hot Tub Surrounds, Garden Furniture and Wood Soffits.

Cloverdale Paint stores and authorized dealers

For the most up-to-date technical information and MSDS sheets, visit our web site at www.cloverdalepaint.com

MANUFACTURED BY



Cloverdale Paint

6950 King George Boulevard

Surrey, BC, Canada

V3W 4Z1

www.cloverdalepaint.com